



# BVX R 500 – SAE 75W-80

Semi-synthetic high performance oil  
for manual transmissions

## USES

Lubrication of modern manual transmissions and drive axles in passenger cars and light commercial vehicles where API GL-4/API GL-4+ SAE 75W-80 grade oil is recommended by the manufacturer (especially **PSA and Renault Groups**).

Particularly suitable for prolonged use under all driving conditions (motorways, city traffic, etc.) and severe usage, all year round.

**Specifications:** API GL4+

Renault Group (Dacia, Nissan, Renault) transmissions Jxx, TL4, NDX  
P.S.A Group (Peugeot, Citroën, DS Automobiles)



## MAIN PHYSICAL DATA

		Methods	Units	75W-80
Density at	20°C	ASTM D4052	kg/m <sup>3</sup>	872
Kinematic viscosity at	40°C	ASTM D445	mm <sup>2</sup> /s	46
Kinematic viscosity at	100°C	ASTM D445	mm <sup>2</sup> /s	8.8
Viscosity index		ASTM D2270		174
Pour point		ASTM D97	°C	-45
Cleveland Open Cup Flash Point		ASTM D92	°C	200

*The data given in this table represents typical production values and should not be taken as specifications.*

## PROPERTIES & ADVANTAGES

- ▶ 100% semi synthetic: half synthetic and half mineral content.
- ▶ Excellent fluidity at low temperatures and outstanding thermal stability.
- ▶ Outstanding extreme-pressure properties for increased protection of gear components.
- ▶ Excellent resistance to oxidation means optimal lubrication in service until the oil is changed.
- ▶ Easier cold starts mean increased energy savings and less pollutant emissions.
- ▶ Enhanced anti-rust and anti-corrosion properties.



[facebook.com/yaccosas](https://facebook.com/yaccosas)

[twitter.com/yaccosas](https://twitter.com/yaccosas)

[youtube.com](https://youtube.com)

